

# Technical Data Sheet (TDS)

Polyether EP-340E(H) - English Version

## Product Name

**Polyether EP-340E(H)**

## Product Introduction

EP-340E(H) is a glycerol-based trifunctional polyether polyol with a molecular weight of 4000, used for the production of ultra-soft foam and air-blocking slow-rebound foam. Adding a small amount during the production of regular slow-rebound foam helps with cell opening.

## Specifications

Item	EP-340E(H)	Test Standard
Appearance	Transparent liquid, free of suspended matter	Q/ZHDDZB 05.10.001-2024
Viscosity (25°C), mPa·s	800~1200	
Water Content, %	≤0.040	
K+, ppm	≤8	
Hydroxyl Value, mgKOH/g	40.00~44.00	
Acid Value, mgKOH/g	≤0.050	
Color, APHA	≤50	
pH Value	5.5~7.5	
Formaldehyde, µg/g	≤0.40	
Acetaldehyde, µg/g	≤2.50	
Acrolein, µg/g	≤0.20	
Acetone, µg/g	≤0.50	
Propionaldehyde, µg/g	≤6.6	
VOC	≤3000	

## Packaging

Packaged in clean, dry, sealed, leak-proof dedicated painted iron drums, net weight 200kg per drum; or in tank trucks, flexitanks, IBCs. Can also be packaged according to customer requirements. Packaging containers must be tightly closed.

## Storage & Transportation

---

During transportation, protect EP-340E(H) from rain and contamination. Handle with care, avoid collision with hard objects to prevent leakage.

Store EP-340E(H) in a ventilated, dry warehouse at room temperature. Avoid damp environments. Storage temperature should be kept below 50°C. Avoid direct sunlight. Keep away from water sources and heat sources. Alternatively, store sealed in containers made of steel, aluminum, polyethylene, or polypropylene. To prevent moisture absorption and oxidation, it is recommended to fill the container headspace with nitrogen. Storage temperatures above 60°C may cause product quality degradation. Short-term heating or cooling has little effect on product quality, but note that viscosity increases significantly at lower temperatures, which may cause some difficulties in processing.

## Shelf Life

---

Under correct storage conditions, the shelf life is 1 year from the date of production. After expiration, the product can still be used if it passes re-inspection.

Note: For low-odor products, customers are advised to use them as soon as possible.

## Safety Information

---

EP-340E(H) is classified as a non-hazardous substance. It has a high flash point and is combustible. In case of fire, use foam, dry powder, steam, or water to extinguish. It is non-explosive. Almost non-toxic. No special ventilation requirements. The toxicity of typical neutral polyether polyols upon ingestion or contact with skin, eyes, or mucous membranes is negligible. In case of skin contact, wash with soapy water. In case of eye contact, flush with low-pressure clean water or seek medical treatment. Workers can wear eye shields or safety glasses for eye protection. Eye wash and shower equipment should be available near the work area. The product is generally considered non-hazardous to skin. When working in areas where contact with the product is possible, pay attention to personal hygiene. Wash skin that has been in contact with the product using cleaning products before eating, drinking, smoking, or leaving the work area.

## Spill Handling

---

Stop the leak if it is safe to do so. For minor leaks, use sand or other absorbent material to absorb and place in a clean, dry container for subsequent disposal. For large spills, collect the spilled material for subsequent disposal. Prevent material from entering groundwater or surface water, as it is not readily biodegradable. All collected spill material should be disposed of in accordance with local environmental regulations.

## Disclaimer

---

The information and technical advice provided above are obtained from reliable sources. However, we make no express or implied warranties regarding the provided data and offer no guarantees herein. If you intend to use our product, we recommend conducting a series of tests. We are not responsible for products applied, used, processed, or manufactured based on the technical information we provide, as these are beyond our control, and the responsibility lies with the user. The conditions and methods of handling, storage, and disposal of this product should be determined by the user.

handling, storage, use, or disposal of this product are beyond our control and may exceed our knowledge. In no event shall we be liable for any losses, damages, or related expenses caused by improper handling, storage, use, or disposal of this chemical.

For more information, please refer to our Technical Safety Data Sheet (TSDS) or contact our Market Service Department.

## Contact Information

---

### **Sinochem Dongda (Zibo) Co., Ltd.**

Address: Hantai Maqiao Chemical Industry Park, Zibo City, Shandong Province, China

Tel: 0086-0533-7878333

E-mail: [dongda@sinochem.com](mailto:dongda@sinochem.com)

Website: <http://www.lxdd.chemchina.com/>

Postal Code: 256405

[Download as PDF](#)